



LED STRIP LUMINAIRE | **BASIC**

**EVERLINE**<sup>®</sup>



\* Shown with lens accessory purchased separately



## Reliable Performance

### Industry-Leading Reliability

Universal's LED Strip Luminaire is a simple indoor, suspended, strip lighting fixture. These products can reduce energy and increase your workspace productivity. This fixture is a good choice for new and retrofit lighting projects.

### Features & Benefits:

- 2', 4', 8' Options
- Energy Efficient:
  - Up to 50% more efficient than fluorescent technology
  - 0-10V Dimming Standard
- Easy Maintenance & Installation:
  - Lumen Maintenance exceeds L70 at 60,000 hours
- Potential for rebates
- No Mercury. Save on costly lamp recycling and/or hazardous waste disposal
- High-reflectance baked enamel finish
- End plate doubles as a coupler or alignment device for continuous row mounting

### Applications:

- Surface Mount or Chain Mount
- Mount individually or in a continuous row
- Indoor, non-condensing, non-corrosive environments
- 120-277V
- Ideal for: Stairwells, Corridors, Light Industrial and Back of House Applications



For a list of DesignLights Consortium<sup>®</sup> QPL listed products please visit [www.designlights.org/qpl/en/saved/UBU24XJ](http://www.designlights.org/qpl/en/saved/UBU24XJ)




## Industry-Leading Reliability

For 70 years, Universal has been on the cutting edge of high efficiency lighting design, pushing the industry towards increasingly higher standards of energy efficiency for LED systems, lighting ballasts, and control systems.

## “Matched Systems”

Universal makes it easy to upgrade to LED technology with our complete in-house design (electronic, thermal and optical) including EVERLINE® “matched” modules and drivers.



## Controllability

Fluorescent systems require specific sockets and wiring treatments when controlled by dimming or frequent switching by occupancy sensors or other control devices. Universal's EVERLINE® fixtures are equipped with 0-10V dimming LED drivers, require no special "lamp wiring" for controllability and are not susceptible to short lamp-life effects when controlled by frequent switching.

PACKAGED DIMENSIONS (in)				
Format	L	W	H	lb
24 in	25	5.25	2.50	4
48 in	49	5.25	2.50	8
96 in	97	5.25	2.50	16

Nominal Dimensions

PRODUCT ENVELOPE (in)			
Format	L	W	H
24 in	24	4.25	2.00
48 in	48	4.25	2.00
96 in	96	4.25	2.00

Nominal Dimensions

## Options:

- Lens plate for optional lens
- 6 Ft, 3 Wire whip
- 6 Ft Cord set
- 10 watt Battery Pack option delivers approximately 1200 lumens for 90 minutes.
- Future wireless connectivity

## Consistent Illumination:

- Color Temperatures (CCTs) of 3000K, 3500K, 4000K and 5000K
- Not vulnerable to color and intensity aberrations associated with routine lamp maintenance of fluorescent systems.

## Performance:

Fixture	Watts	Lumens	LPW
24 in	18.6	2,590	139
	24	3,355	140
	28	3,705	132
48 in	24	3,475	145
	35	4,920	141
	48	6,475	135
96 in.	59	7,755	131
	48	6,475	135
	70	9,840	141
	97	12,950	134
	118	15,510	131

## Product Ordering Information:

Ordering Information										
Series	Format	-	Watts	W	CRI	Color Temp.	-	Voltage	-	Options
STRP4 = 4.25 Inch, Strip Style Luminaire	24 in	-	18 <sup>1</sup> 24 <sup>4</sup> 28 <sup>1</sup>	W	8 = 80 (minimum)	30 = 3000K 35 = 3500K 40 = 4000K 50 = 5000K (Nominal)	-	U = 120-277 VAC 50/60 Hz	-	LNPL <sup>7</sup> = Lens plates (longer end plates to accommodate a separately purchased lens) WP = 6 FT, 3 Wire, whip C6F <sup>6</sup> = 6 FT cord set EM <sup>5</sup> = Backup battery pack
	48 in	-	24 <sup>4</sup> 35 <sup>2</sup> 48 <sup>5</sup> 57 <sup>2</sup>							
	96 in	-	48 <sup>5</sup> 70 <sup>3</sup> 97 <sup>3</sup> 114 <sup>3</sup>							

### ORDERING NOTES:

1. 24 inch length only
2. 48 inch length only
3. 96 inch length only
4. 24 & 48 inch lengths only
5. 48 & 96 inch lengths only
6. For use on 120VAC systems only
7. Fixtures with the LNPL option do not come equipped with standard end plates (which can be used for alignment). For continuous row mounting of fixtures with lenses, order standard fixtures, matching lenses (see above) and as many STRP4-ACC-LNPL accessories (see above) as needed to finish the rows.

ACCESSORIES				
STRP4-ACC-WG4	4-Ft Wire guard	STRP4-ACC-LEN8	8-Ft Lens	STRP4-ACC-LNPL
STRP4-ACC-LEN2	2-Ft Lens	STRP4-ACC-PNDKIT	2ps V-Hook & 2pc 2-Ft Chain	
STRP4-ACC-LEN4	4-Ft Lens			

2pc End plate for use with lens



It's **EASY** to **REACH US...**

LIT#: SLF072617

**UNIVERSAL LIGHTING TECHNOLOGIES, INC.**  
51 Century Blvd., Suite 230  
Nashville, TN 37214-3683

GENERAL INFO: (615) 316-5100

For Technical Engineering Services (TES), application support and warranty information, call **1-800-225-5278**

WEBSITE: [unvlt.com](http://unvlt.com)  
EMAIL: [webmaster@unvlt.com](mailto:webmaster@unvlt.com)