



LED WRAPAROUND | **COMMERCIAL**

EVERLINE[®]



Commercial Ready

Industry-Leading Reliability

Universal's LED Wraparound Luminaire is a surface mounted fixture. These fixtures are cost efficient and a good choice for LED energy efficiency with the 0-10V dimming standard feature.

Features & Benefits:

- 2' & 4' options
- Energy Efficient:
 - Up to 50% more efficient than fluorescent technology
 - 0-10V Dimming standard
- Easy Maintenance & Installation:
 - Lumen maintenance exceeds L70 at 60,000 hours
 - Diffuser self-aligns and hinges from either side
- Potential for rebates
- No Mercury. Save on costly lamp recycling and/or hazardous waste disposal.
- Nominal 9" width with a shallow, 3.13 inch profile.
- Corrosion and scratch resistant
- Acrylic, prismatic diffuser with ribbed linear sides

Applications:

- Surface Mount, Stem Mount, or Chain Mount
- Indoor, non-condensing, non-corrosive environments
- 120-277V
- Ideal for spaces such as stairwells, storage, closet rooms, utility and parking garages.



For a list of DesignLights Consortium[®] QPL listed products please visit www.designlights.org/qpl/en/saved/UBU24XJ




Industry-Leading Reliability

For 70 years, Universal has been on the cutting edge of high efficiency lighting design, pushing the industry towards increasingly higher standards of energy efficiency for LED systems, lighting ballasts, and control systems.

“Matched Systems”

Universal makes it easy to upgrade to LED technology with our complete in-house design (electronic, thermal and optical) including EVERLINE® “matched” modules and drivers.



Controllability

Fluorescent systems require specific sockets and wiring treatments when controlled by dimming or frequent switching by occupancy sensors or other control devices. Universal's EVERLINE® fixtures are equipped with 0-10V dimming LED drivers, require no special "lamp wiring" for controllability and are not susceptible to short lamp-life effects when controlled by frequent switching.

PACKAGED DIMENSIONS (in)				
Format	L	W	H	lb
24 in	25.0	10.0	3.5	7.0
48 in	49.0	10.0	3.5	12.0

Nominal Dimensions

PRODUCT ENVELOPE (in)			
Format	L	W	H
24 in	24.0	10.0	3.5
48 in	48.0	10.0	3.5

Nominal Dimensions

Options:

- 6 Ft, 3 Wire whip
- 6 Ft Cord set
- Future wireless connectivity

Consistent Illumination:

- Color Temperatures (CCTs) of 3000K, 3500K, 4000K and 5000K
- Not vulnerable to color and intensity aberrations associated with routine lamp maintenance of fluorescent systems.

Performance:

Fixture	Watts	Lumens	LPW
24"	28	3465	124
48"	48	5107	106
	56	6019	107

Product Ordering Information:

Ordering Information										
Series	Length	-	Watts	W	CRI	Color Temp.	-	Voltage	-	Options
WRP9 = Surface Mount, 9-Inch, Wraparound Luminaire	24 in	-	28 ¹	W	8 = 80 (minimum)	30 = 3000K 35 = 3500K 40 = 4000K 50 = 5000K (Nominal)	-	U = 120-277 VAC 50/60 Hz	-	WP = 6 FT, 3 Wire, whip C6F ² = 6 FT cord set
	48 in	-	48 ² 56 ²							

ORDERING NOTES:

1. 24 inch length only
2. 48 inch lengths only
3. For use on 120VAC systems only



It's **EASY**
to **REACH US...**

UNIVERSAL LIGHTING TECHNOLOGIES, INC.
51 Century Blvd., Suite 230
Nashville, TN 37214-3683

GENERAL INFO: (615) 316-5100

For Technical Engineering Services (TES), application support and warranty information, call **1-800-225-5278**

WEBSITE: unvlt.com
EMAIL: webmaster@unvlt.com

LIT#: WRF051917