



Visual Comfort

Industry-Leading Reliability

Universal's PLA family of LED Professional Volumetric Luminaires provides the visual comfort of diffuse lighting and excellent uniformity along with a modern design appeal.

Features & Benefits:

- 2'x2', 2'x4', 1'x4' Options
- Energy Efficient:
 - Up to 50% more efficient than fluorescent technology
 - 0-10V Dimming standard
- Easy Maintenance & Installation:
 - Lumen maintenance exceeds L70 at 90,000 hours
 - Removable access plate makes power wires easy to get to from above the fixture
- Corrosion and scratch resistant
- Potential for rebates
- No Mercury. Save on costly lamp recycling and/or hazardous waste disposal.
- Visual Comfort
 - Update environments by getting rid of the "cave effect" exhibited by deep bodied parabolic and other aging fixture designs
 - Low loss frosted acrylic center-basket diffuser
 - Volumetric fixtures provide better uniformity
 - Designed to visually match the PRK (Professional Retrofit Kit)

Applications:

- For recessed, lay-in mounting in T-Grid ceilings
- Indoor, non-condensing, non-corrosive environments
- 120-277V or 347-480 VAC
- Ideal for: Commercial, Retail, Hospitality & Office



For a list of DesignLights Consortium[®] QPL listed products please visit www.designlights.org/qpl/en/saved/UBU24XJ




Industry-Leading Reliability

For 70 years, Universal has been on the cutting edge of high efficiency lighting design, pushing the industry towards increasingly higher standards of energy efficiency for LED systems, lighting ballasts, and control systems.

“Matched Systems”

Universal makes it easy to upgrade to LED technology with our complete in-house design (electronic, thermal and optical) including EVERLINE® “matched” modules and drivers.



Consistent Look

The EVERLINE® Professional Volumetric Luminaire (PLA) is designed to have a matching look and feel as the EVERLINE® Professional Retrofit Kit (PRK). This provides you a retrofit solution, allowing you to keep the body of a fixture while updating the optics and light engine, or to replace the entire fixture and maintain a consistent look and performance across your space.

PRODUCT ENVELOPE (in)				
Format	L	W	H	LB
1x4 ft	48	12.0	3.6	11
2x2 ft	24	24.0	3.6	10
2x4 ft	48	24.0	3.6	17

Nominal Dimensions

Options:

- 6 Ft, 3 Wire whip
- Future wireless connectivity
- 10 watt Battery Pack option delivers approximately 1200 lumens for 90 minutes.

Consistent Illumination:

- Color Temperatures (CCTs) of 3000K, 3500K, 4000K and 5000K
- Not vulnerable to color and intensity aberrations associated with routine lamp maintenance of fluorescent systems.

Performance:

Fixture	Watts	Lumens	LPW
1'x4'	36	4715	131
2'x2'	36	4765	130
2'x4'	33	4470	135
	46	6043	131

Product Ordering Information:

Ordering Information	Series	Format	Watts	W	CRI	Color Temp.	Voltage	Options
PLA = Professional Luminaire	14 = 1ft x 4ft	-	36	W	8 = 80 (minimum)	30 = 3000K	U = 120-277 VAC 347 = 347 VAC	EM ¹ = Backup Battery Pack WP6 = 6ft Whip
	22 = 2ft x 2ft	-	36			35 = 3500K		
	24 = 2ft x 4ft	-	33			40 = 4000K		
		-	46			50 = 5000K		

ORDERING NOTES:

1. EM option only available for 120-277 VAC luminaires.



It's **EASY**
to **REACH US...**

UNIVERSAL LIGHTING TECHNOLOGIES, INC.
51 Century Blvd., Suite 230
Nashville, TN 37214-3683

GENERAL INFO: (615) 316-5100

For Technical Engineering Services (TES), application support and warranty information, call **1-800-225-5278**

WEBSITE: unvlt.com
EMAIL: webmaster@unvlt.com

LIT#: EFPLAF032618