

January 13, 2020

Patent List:

Patent No.	Issued Date	Title
6,291,944	9/18/01	System & Method for Limiting Through-Lamp Ground Fault Currents in Non-Isolated Electronic Ballasts
7,019,662	3/28/06	LED Drive for Generating Constant Light Output
7,391,168	6/24/08	Digital Control of Electronic Ballasts Using AC Power Lines as a Communication Medium
7,394,204	7/1/08	Zero crossing detection of line voltage/current of variable amplitude
7,432,660	10/7/08	IC-based low cost reliable electronic ballast with multiple striking attempts and end of lamp life protection
7,443,113	10/28/08	Software controlled electronic dimming ballast
7,679,294	3/16/10	Method and system to eliminate fluorescent lamp striations by using capacitive energy compensation
7,705,544	4/27/10	Lamp circuit with controlled ignition pulse voltages over a wide range of ballast-to-lamp distances
7,719,204	5/18/10	Method for controlling striations in a lamp powered by an electronic ballast
7,768,755	8/3/10	Over-voltage protection and automatic re-strike circuit for an electronic ballast
7,786,391	8/31/10	Ballast housing having rolled edge lead wire exit
7,843,141	11/30/10	Low cost step dimming interface for an electronic ballast
8,116,089	2/14/12	Method and apparatus for securing a magnetic component to a printed circuit board for soldering
8,129,920	3/6/12	Discharge lamp ballast and fixture with controlled preheating
8,138,679	3/20/12	Organic electroluminescent light emitting device for restoring normal operation after low-voltage errors
8,143,796	3/27/12	Electronic ballast with controlled filament preheating using half-wave lamp current detection
8,143,809	3/27/12	LED illuminating device

8,154,214	4/10/12	Switching power supply for an illumination device with precision current control
8,183,791	5/22/12	System and method for preventing low dimming current startup flash
8,193,727	6/5/12	Lamp end of life protection circuit and method for an electronic dimming ballast
8,198,824	6/12/12	Electronic ballast for restarting high-pressure discharge lamps in various states of operation
8,203,273	6/19/12	Ballast circuit for a gas discharge lamp that reduces a pre-heat voltage to the lamp filaments during lamp ignition
8,203,282	6/19/12	Electronic ballast with lamp end of life detection and protection circuits
8,207,680	6/26/12	Discharge lamp ballast having an auto-transformer for high voltage detection
8,207,690	6/26/12	High-pressure discharge lamp ballast with rapid lamp restart circuit
8,212,643	7/3/12	Bobbin for an inductive electronic component
8,222,834	7/17/12	HID lamp ballast with controlled DC step down circuit
8,222,835	7/17/12	Electronic ballast with adjustable filament preheating based on output current symmetry
8,228,003	7/24/12	Electronic ballast for an hid lamp with lamp re-start control
8,232,727	7/31/12	Ballast circuit for a gas-discharge lamp having a filament drive circuit with monostable control
8,232,741	7/31/12	Electronic ballast with controlled lamp preheating
8,242,870	8/14/12	Magnetic component with a notched magnetic core structure
8,253,351	8/28/12	Electronic ballast with multimode lamp power control
8,258,712	9/4/12	Ballast circuit for reducing lamp striations
8,274,234	9/25/12	Dimming ballast with parallel lamp operation
8,274,237	9/25/12	LED driver circuit with over-current protection during a short circuit condition
8,278,835	10/2/12	Modular electronic ballast

8,288,956	10/16/12	Lamp preheat circuit for a program start ballast with filament voltage cut-back in steady state
8,294,385	10/23/12	High-pressure discharge lamp ballast with multi-mode lamp starting circuit
8,299,723	10/30/12	Electronic ballast with lamp flicker suppression during start-to-steady state transition
8,299,727	10/30/12	Anti-arcing protection circuit for an electronic ballast
8,310,160	11/13/12	Anti-arcing circuit for current-fed parallel resonant inverter
8,319,447	11/27/12	Hid lamp ballast with multi-phase operation based on a detected lamp illumination state
8,324,813	12/4/12	Electronic ballast with frequency independent filament voltage control
8,324,829	12/4/12	Startup control for a high pressure discharge lamp ballast
8,330,378	12/11/12	Illumination device and method for controlling a color temperature of irradiated light
8,330,382	12/11/12	Electronic ballast for correcting asymmetrical current flow across a gas discharge lamp
8,339,056	12/25/12	Lamp ballast with protection circuit for input arcing and line interruption
8,344,628	1/1/13	Dimming electronic ballast with lamp end of life detection
8,344,644	1/1/13	Electronic ballast for HID lamps with active lamp power control
8,350,678	1/8/13	Power line dimming controller and
8,354,795	1/15/13	Program start ballast with true parallel lamp operation
8,378,579	2/19/13	Ballast circuit for a gas discharge lamp with a control loop to reduce filament heating voltage below a maximum heating level
8,390,213	3/5/13	LED power-source circuit and illumination fixture using the same
8,400,074	3/19/13	Electronic ballast with feedback current control for preheating of lamp filaments
8,405,488	3/26/13	System and method for encoding ballast control signals
8,406,007	3/26/13	Magnetic circuit board connector component

8,427,074	4/23/13	PLC controller and discharge lighting ballast receiver with high noise immunity
8,436,550	5/7/13	LED lamp driving circuit with dimming capability
8,441,203	5/14/13	Dimming electronic ballast for true parallel lamp operation
8,449,145	5/28/13	Mounting apparatus for a light emitting diode module
8,450,946	5/28/13	Zone addressing circuit for an electronic ballast
8,471,475	6/25/13	Modular dimming ballast with decoupled half-bridge topology
8,482,213	7/9/13	Electronic ballast with pulse detection circuit for lamp end of life and output short protection
8,482,222	7/9/13	Lighting device and light fixture using lighting device
8,482,944	7/9/13	Electronic ballast with inrush protection circuit
8,487,539	7/16/13	Power supply for an LED illumination device
8,498,124	7/30/13	Magnetic circuit board stacking component
8,502,463	8/6/13	LED driver circuit with open load detection and associated control method
8,502,475	8/6/13	Discharge lamp ballast with feedback current control during an electrode heating operation
8,536,801	9/17/13	System and method for individually modulating an array of light emitting devices
8,564,216	10/22/13	Asymmetric end-of-life protection circuit for fluorescent lamp ballasts
8,581,497	11/12/13	Electronic ballast circuit and method for detecting removal of parallel connected lamp filaments in low level dimming
8,593,078	11/26/13	Universal dimming ballast platform
8,610,165	12/17/13	LED light module with heat releasing casing and grooved backing to contain conductive bonding fluids
8,610,366	12/17/13	Lighting ballast and method for balancing multiple independent resonant tanks
8,624,272	1/7/14	LED assembly with color temperature correction capability

8,638,039	1/28/14	Electronic ballast and method for providing a DC voltage component during lamp startup
8,638,042	1/28/14	System and method for regulating an open circuit voltage of an HID lamp ballast
8,654,485	2/18/14	Electronic ballast with protected analog dimming control interface
8,664,883	3/4/14	LED lighting device with chopper circuit and dimming control method
8,669,721	3/11/14	Solid state light source based lighting device and lighting system
8,680,775	3/25/14	Lighting driver circuit and light fixture
8,680,776	3/25/14	Lighting device including a fast start circuit for regulating power supply to a PFC controller
8,680,788	3/25/14	Semiconductor light-emitting element driver circuit and light fixture using the same
8,686,667	4/1/14	Lighting power source with controlled charging operation for driving capacitor
8,698,424	4/15/14	Power line dimming controller and receiver
8,699,244	4/15/14	Electronic ballast with load-independent and self-oscillating inverter topology
8,716,937	5/6/14	Lighting ballast with reduced filament drive and pin current balancing
8,766,561	7/1/14	LED lighting device with output impedance control
8,847,512	9/30/14	Program start ballast having resonant filament heating circuit with clamped quality factor
8,847,750	9/30/14	Network of dual technology occupancy sensors and associated lighting control method
8,853,949	10/7/14	LED driver with end-of-life detection circuitry
8,894,251	11/25/14	Lighting device topology for reducing unevenness in LED luminance and color
8,909,382	12/9/14	Occupancy detection system and method having automatic adaptation capabilities
8,922,131	12/30/14	Series resonant inverter with capacitive power compensation for multiple lamp parallel operation
8,928,236	1/6/15	LED driver circuit with unified controller

8,928,250	1/6/15	Method and circuit for LED load management
8,947,015	2/3/15	Indirect line voltage conduction angle sensing for a chopper dimmed ballast
8,947,020	2/3/15	End of life control for parallel lamp ballast
9,095,022	7/28/15	Constant current driver based on critical condition mode buck converter
9,099,333	8/4/15	LED lamp device having a fluorescent element shaped 12/878,168 for uniform light conversion
9,125,250	9/1/15	Constant current control based on indirect current sensing for critical conduction mode buck converter
9,125,259	9/1/15	Constant current drive circuit for multi-channel LED lighting
9,173,256	10/27/15	Dimmable LED driver based on parallel resonant current fed self-oscillating topology
9,183,974	11/10/15	Bobbin apparatus for reducing gap losses in magnetic components
9,190,830	11/17/15	Overcurrent protection circuit and method for an LED driver
9,203,321	12/1/15	Non-isolated resonant DC-DC converter with boost-type voltage doubler output
9,237,613	1/12/16	Constant current control for an LED driver circuit using a microcontroller-based oscillator controlled by a differential error feedback signal from a proportional and integration control loop
9,237,621	1/12/16	Current control circuit and method for floating IC driven buck-boost converter
9,237,636	1/12/16	Self-clamped resonant filament heating circuit
9,240,726	1/19/16	Dimming LED driver circuit with dynamically controlled resonant tank gain
9,279,564	3/8/16	Indirect area lighting apparatus and methods
9,291,335	3/22/16	Light-emitting device with electrically insulated LED module
9,293,246	3/22/16	Magnetic component with integrated component circuit board
9,295,143	3/22/16	Wireless controlled lighting system with shared signal path on output wires

9,295,145	3/22/16	Multifunction magnetic device with multiple cores and coils
9,307,587	4/5/16	Constant current source based on self-oscillating soft-switching LLC converter topology
9,307,623	4/5/16	Method to control striations in a lamp powered by an electronic ballast
9,362,044	6/7/16	Magnetic component with multiple pin row bobbin
9,363,862	6/7/16	Automatic current and reference gain control for wide range current control
9,369,050	6/14/16	Indirect current sensing method for a constant current flyback converter
9,370,061	6/14/16	High power factor constant current buck-boost power converter with floating IC driver control
9,379,533	6/28/16	Input surge protection circuit and method for an LED load
9,396,865	7/19/16	Magnetic component with auxiliary winding circuit board
9,401,237	7/26/16	Core passage step apparatus and methods
9,416,951	8/16/16	Compact indirect lighting system with improved thermal performance
9,419,514	8/16/16	High power factor DC power supply with variable gain converter and fast-averaging control loop
9,420,670	8/16/16	Controller and receiver for a power line communication system
9,431,893	8/30/16	Stability control of a power factor correction circuit using adaptive multiplier voltage feedback
9,435,527	9/6/16	Thermal venting apparatus and method for LED modules
9,459,396	10/4/16	Linear indirect LED lighting system
9,462,655	10/4/16	Circuit and method for monitoring functionality of an electronic surge suppressor
9,480,126	10/20/16	Method to detect uneven AC load or parallel load removal
9,490,058	11/8/16	Magnetic component with core grooves for improved heat transfer
9,518,716	12/13/16	Linear wide area lighting system

9,520,711	12/13/16	Gate drive integrated circuit with input line overvoltage protection for a half-bridge power converter
9,521,724	12/13/16	Method for automatically commissioning devices used in building lighting and controls
9,577,540	2/21/17	Multi-stage flyback converter for wide input voltage range applications
9,583,073	2/28/17	Adaptive startup method for constant current LED drivers
9,583,852	2/28/17	PCB holder having a leg with a passageway with a conductive pin therein to electrically connect two PCBs
9,618,164	4/11/17	Adapter for retrofitting LED lamps, method of use, and lighting fixture with retrofit adapter
9,629,206	4/18/17	Reducing output ripple current and protecting inverter switches during non-zero voltage switching for isolated buck converters
9,629,209	4/18/17	Offline tuning interface for LED drivers
9,644,833	5/9/17	Encapsulated LED lighting module with integral gas venting
9,645,597	5/9/17	Circuit and method for indirectly sensing current and voltage in a floating output power supply
9,648,678	5/9/17	LED driver circuit with dimming control and programming interfaces
9,668,309	5/30/17	LED driver providing constant output power across a wide output voltage and current range
9,674,907	6/6/17	Input surge protection circuit and method for a non-isolated buck-boost LED driver
9,680,244	6/13/17	Header apparatus for providing electrical connection to a printed circuit board, and daughter card and circuit assembly incorporating the header apparatus
9,681,512	6/13/17	Combined wireless voltage controlled dimming interface for an LED driver
9,681,520	6/13/17	Photosensor employing a fiber optic collector
9,683,717	6/20/17	Asymmetric area lens for low-profile lighting system
9,689,554	6/27/17	Asymmetric area lighting lens
9,693,404	6/27/17	Negative current sensing method for multi-channel LED driver

9,693,411	6/27/17	LED driver configuration and dimming interface for dynamic adjustment of driver operating parameters
9,719,662	8/1/17	Thin-form lens for volume lighting applications
9,721,716	8/1/17	Magnetic component having a core structure with curved openings
9,723,667	8/1/17	Output tuning and dimming interface for an LED driver
9,723,695	8/1/17	Power line communication method and apparatus using downstream current modulation
9,746,136	8/29/17	Illumination device having multiple LED elements with varying color temperatures
9,756,703	9/5/17	Lighting control system and method for communication of short messaging
9,769,890	9/19/17	Circuit and method for eliminating power-off flash for LED drivers
9,769,896	9/19/17	LED driver with offline tuning interface using hot and neutral inputs
9,787,195	10/10/17	Primary current sensing method for isolated LED driver
9,788,430	10/10/17	Stacked magnetic assembly
9,799,442	10/24/17	Magnetic core structures for magnetic assemblies
9,801,262	10/24/17	Conduit knockout interface device for connecting a power over ethernet cable to an LED luminaire
9,805,859	10/31/17	Magnetic component with elevated bobbin
9,807,830	10/31/17	LED driver circuit with step configurable output
9,816,681	11/14/17	Side lit indirect flexible lighting system
9,820,351	11/14/17	Circuit and method for abnormal fault testing in an LED driver
9,826,583	11/21/17	Auxiliary power supply with dynamically adjustable output
9,835,322	12/5/17	Flow through extended surface troffer system
9,837,194	12/5/17	Output transformer and resonant inductor in a combined magnetic structure

9,837,913	12/5/17	Control method to avoid capacitive mode switching for resonant converters
9,842,683	12/12/17	Bobbin and E-core assembly configuration and method for E-cores and EI-cores
9,844,118	12/12/17	AC LED driver circuit
9,894,718	2/13/18	Constant current source LED driver circuit with self-clamped output
9,913,335	3/6/18	LED driver circuit with three level step dimming interface
9,913,346	3/6/18	Surge protection system and method for an LED driver
9,913,354	3/6/18	Unpowered tuning interface circuit for an LED driver
9,974,129	5/15/18	Circuit and method for LED current regulation and ripple control
9,974,147	5/15/18	Integrated LED driver for wireless communication
9,978,496	5/22/18	Stacked magnetic assembly
9,980,328	5/22/18	Apparatus, system, and method for configuring an unpowered LED driver using an RS-232 interface
9,980,396	5/22/18	Low profile magnetic component apparatus and methods
9,991,045	6/5/18	Bobbin and core assembly configuration and method for E-core and I-core combination
9,991,236	6/5/18	LED lamp device having a fluorescent element shaped for uniform light conversion
10,004,123	6/19/18	Failure detection and alerting circuit for a differential mode surge protection device in an LED driver
10,039,159	7/31/18	AC LED driver with capacitive switching
10,041,984	8/7/18	Input voltage sense circuit for boost power factor correction in isolated power supplies
10,045,451	8/7/18	Lighting control system, expansion pack, and method of use
10,083,790	9/25/18	Method and apparatus for attaching magnetic components to printed circuit boards
10,098,194	10/9/18	Current and voltage control circuit and method for a class II LED driver

10,098,202	10/9/18	Constant current source with output voltage range and self-clamping output voltage
10,103,538	10/16/18	Surge protection circuit for a half-bridge power converter
10,128,740	11/13/18	Dynamic AC impedance stabilization in a flyback LED driver
10,178,720	1/8/19	Low standby power control circuit for LED driver
10,186,809	1/22/19	Printed circuit board connector with integrated EMI noise suppression
10,186,812	1/22/19	Ferrite wafer and connector assembly for EMI noise suppression on a printed circuit board
10,243,473	3/26/19	Gate drive IC with adaptive operating mode
10,264,641	4/16/19	Lighting system and method for dynamically regulating driven current to an analog or digital dimming interface
10,320,181	6/11/19	Failure detection and alerting circuit for a common mode surge protection device in an LED driver
10,320,283	6/11/19	Resonant converter with pre-charging circuit for startup protection
10,320,303	6/11/19	Frequency controlled dummy load to stabilize PFC operation at light load conditions
10,326,377	6/18/19	Circuit and method for indirect primary-side load current sensing in an isolated power supply
10,356,873	7/16/19	Multiple interface LED driver with inherent overvoltage protection
10,362,644	7/23/19	Flyback converter with load condition control circuit
10,362,652	7/23/19	Lighting device with dimming reference control method to stabilize low output current

Products & Supporting Patents

188639.05	
	8,482,944
	8,638,042
188639.05	
	8,482,944
	8,638,042

188652.05	
	8,482,944
	8,638,042
188895.02	
	8,482,944
188896.02	

	8,482,944
188897.02	
	8,482,944
188901.02	
	8,482,944
188901.02	

	9,980,396
188902.02	
	8,482,944
188903.02	
	8,482,944
188989.05	
	8,482,944
	8,638,042
ACMDCLUNV	
	8,405,488
AW3V-DX-254ND	
	7,679,294
AWRV-DF-232HA	
	7,679,294
AWRV-DF-232NA	
	7,679,294
AWRV-DX-232HA	
	7,679,294
AWRV-DX-232NA	
	7,679,294
AWRV-LP-232HA	
	7,679,294
AWRV-PS-232HA	
	7,679,294
AWRV-PS-232NA	
	7,679,294
AWUV-DF-254ND	
	7,679,294
AWUV-DX-254ND	
	7,679,294
B114PUNVDV3-D	
	8,278,835
B114PUNVSV3-D	
	8,183,791
	8,278,835
B128PUNV50-D	
	8,278,835
B128PUNVDRH-D	
	8,278,835

	8,405,488
	8,450,946
B128PUNVDV3-D	
	8,278,835
B128PUNVSV3-D	
	8,183,791
	8,278,835
B132I120RC-B	
	7,786,391
	8,212,643
B132IUNVEL-A	
	7,719,204
	7,786,391
B132IUNVHE-A	
	7,719,204
	7,786,391
B132IUNVHE-N	
	7,786,391
B132IUNVHP-B	
	7,786,391
B132IUNVHP-N	
	7,719,204
	7,786,391
B132PUNVDV3-A	
	8,278,835
B132PUNVEL-B	
	7,719,204
B132PUNVHE-B	
	7,719,204
B132PUNVHP-A	
	7,719,204
	7,786,391
B132PUNV-N	
	8,324,813
B132PUNVSV3-A	
	8,183,791
	8,278,835
B135PUNVDV3-D	
	8,278,835

B135PUNVSV3-D	
	8,183,791
B214PU115S50A	
	7,679,294
	7,786,391
B214PUNVDV3-D	
	8,278,835
B214PUNVSV3-D	
	8,183,791
B224PUNV-C	
	7,432,660
B228P2SV3PLA	
	8,278,835
B228P347PLA	
	8,278,835
B228P3DV3PLA	
	8,278,835
B228PU115S50D	
	7,679,294
B228PU95S50D	
	7,679,294
B228PUDV3PLA	
	8,278,835
B228PUNV90-C	
	7,432,660
B228PUNVC	
	8,339,056
B228PUNV-C	
	8,847,512
B228PUNVDRH-D	
	8,278,835
	8,405,488
	8,450,946
B228PUNVDV3-D	
	8,278,835
B228PUNV-N	
	7,786,391
B228PUNVPLA	
	8,278,835

B228PUNVS50
7,679,294
8,339,056
B228PUNVSV3
7,679,294
B228PUNVSV3-D
8,183,791
8,278,835
B228PUSV3PLA
8,278,835
8,441,203
B232I120EL
8,212,643
B232I120RC-B
7,786,391
8,212,643
B232I120RCL-B
7,786,391
8,212,643
B232I120RHH-A
7,786,391
B232I347HP-A
7,786,391
B232I347L-A
7,786,391
B232I347RH-A
7,786,391
B232IUNV104-A
7,786,391
8,212,643
B232IUNVEL-A
7,719,204
7,786,391
8,212,643
B232IUNVEXP-B
7,786,391
B232IUNVHE-A
7,719,204
7,786,391

B232IUNVHEH-A
7,786,391
8,212,643
B232IUNVHE-N
7,786,391
B232IUNVHP-B
7,719,204
7,786,391
B232IUNVHP-BR
7,786,391
B232IUNVHP-N
7,719,204
7,786,391
B232IUNVHP-NO
7,786,391
B232IUNVHP-NR
7,786,391
B232IUNVLC-B
7,786,391
B232P347HPLA
8,278,835
B232P3DV3PLA
8,278,835
B232P3DV3PLD
8,278,835
B232P3S50PLA
7,786,391
8,278,835
B232P3S50PLHA
7,786,391
8,278,835
B232P3SV3PLA
8,278,835
B232PU104S50A
7,786,391
B232PUDV3PLA
8,278,835
B232PUDV3PLD
8,278,835

B232PULV50-A
7,786,391
B232PULV50H-A
7,786,391
B232PUNVA
8,339,056
B232PUNVDFH
8,278,835
B232PUNVDFH-A
7,786,391
8,405,488
8,450,946
B232PUNVDR-A
7,786,391
8,278,835
8,405,488
8,450,946
B232PUNVDRH-A
7,786,391
8,278,835
8,405,488
8,450,946
B232PUNVDRL-A
7,786,391
8,278,835
8,405,488
8,450,946
B232PUNVDV3-A
8,278,835
B232PUNVDY-A
8,278,835
8,405,488
8,450,946
B232PUNVDYH-A
8,278,835
8,405,488
8,450,946
B232PUNVDYL-A
8,278,835

B232PUNVEL-A
7,719,204
7,786,391
B232PUNVEL-B
7,719,204
7,786,391
8,324,813
B232PUNVHE-A
7,719,204
7,786,391
8,699,244
B232PUNVHE-B
7,719,204
7,786,391
8,324,813
B232PUNVHEH
8,299,727
8,354,795
8,593,078
B232PUNVHEH-A
7,786,391
8,212,643
8,324,813
B232PUNVHP-A
7,719,204
7,786,391
B232PUNVHP-B
7,719,204
B232PUNVHPLA
8,278,835
B232PUNVS50
8,339,056
B232PUNVSV3
7,679,294
B232PUNVSV3-A
8,183,791
8,278,835
B232PUS50-A
7,786,391

B232PUS50PLA
7,786,391
8,278,835
B232PUS50PLHA
7,786,391
8,278,835
B232PUSV3PLA
8,441,203
B232PUSVEPLA
8,278,835
B232PWRVDYHB
8,278,835
B232PWRVSV3-B
8,278,835
B234SR120M-A
7,719,204
7,786,391
9,805,859
B240R220-A
7,786,391
B244I120HE
8,212,643
B244I277HE-A
7,786,391
8,212,643
B244IUNVHE-A
7,786,391
B254P347-D
7,432,660
B254P3SV3PLD
8,278,835
B254PUDV3PLD
8,278,835
B254PUNVD
8,339,056
B254PUNV-D
8,288,956
B254PUNVDR-D
8,278,835

8,405,488
8,450,946
B254PUNVPL-A
7,786,391
9,307,623
B254PUNVPLHB-A
9,307,623
B259IUNVEL
7,719,204
B259IUNVEL-A
7,786,391
8,212,643
B259IUNVHE
7,719,204
B259IUNVHE-A
7,786,391
8,212,643
B259IUNVHP
7,719,204
B259IUNVHP-A
7,786,391
8,212,643
B260I120M-A
8,212,643
B260I120RH
8,212,643
B260IUNVHP
7,719,204
B328PUNVS30-A
8,278,835
B332I120L-A
7,786,391
B332I277L-A
7,786,391
B332I277RHU-A
7,786,391
B332IUNVEL-A
7,786,391
8,212,643

B332IUNVHE-A	
	7,786,391
	8,212,643
B332IUNVHEH-A	
	7,786,391
	8,212,643
B332IUNVHP-A	
	7,786,391
	8,212,643
B332IUNVLC-A	
	7,786,391
	8,212,643
B332PUNVDR-A	
	8,278,835
	8,405,488
	8,450,946
B332PUNVDRH-E	
	8,278,835
	8,405,488
	8,450,946
B332PUNVDRL-A	
	8,278,835
	8,405,488
	8,450,946
B332PUNVEL-A	
	7,786,391
	8,324,813
B332PUNVHE-A	
	7,786,391
	8,212,643
	8,324,813
	8,699,244
B332PUNVHEH	
	8,299,727
	8,354,795
	8,593,078
B332PUNVHEH-A	
	8,324,813
B432I120L-A	

	7,786,391
B432I120RC-A	
	7,786,391
	8,212,643
B432I120RCL-A	
	7,786,391
	8,212,643
B432I120RES-A	
	7,786,391
B432I120RH-A	
	7,786,391
	8,212,643
B432I277L-A	
	7,786,391
B432I277RH-A	
	7,786,391
B432IUNVEL-A	
	7,786,391
	8,212,643
B432IUNVHE-A	
	7,786,391
B432IUNVHP-A	
	7,786,391
	8,212,643
B432IUNVHP-A/277RH-A	
	8,212,643
B432IUNVLC-A	
	7,786,391
	8,212,643
B432PUNVDR-E	
	8,278,835
	8,405,488
	8,450,946
B432PUNVDRL-E	
	8,278,835
	8,405,488
	8,450,946
B432PUNVEL-A	
	8,212,643

	8,324,813
B432PUNVHE-A	
	8,212,643
	8,324,813
B432PUNVHE-E	
	8,699,244
B432PUNVHEH	
	8,299,727
	8,354,795
	8,593,078
B432PUNVHEH-A	
	9,307,623
B432PUNVHEH-E	
	8,212,643
B454PUNVDR-E	
	8,278,835
B454PUNV-E	
	7,432,660
	8,288,956
	9,237,636
	9,307,623
	9,805,859
B454PUNVHB-E	
	7,432,660
	8,922,131
	9,237,636
	9,805,859
B454PUNVHE-E	
	9,480,126
B454PUNVPL-E	
	8,922,131
	9,183,974
	9,307,623
B454PUNVPLHB	
	8,922,131
B454PUNVPLHB-E	
	9,307,623
C213UNVDV3ME	
	8,278,835

8,339,056
C213UNVME
7,432,660
C213UNVSV3ME
8,183,791
8,278,835
8,339,056
C218UNVDV3ME
8,278,835
8,339,056
C218UNVME
7,432,660
C218UNVSV3ME
8,183,791
8,278,835
8,339,056
C226UNVDV3ME
8,278,835
8,339,056
C226UNVSV3ME
8,183,791
8,278,835
8,339,056
C240PUNVDR-A
7,786,391
8,405,488
8,450,946
C240PUNVHP-B
7,786,391
C240SI120RH
8,212,643
C240SI277RH
8,212,643
C2642UNV
8,203,273
C340SI120RH
8,212,643
C340SI277RH
8,212,643

D060C03250-SQ020C
9,974,129
10,128,740
D10CC150HV10F
9,237,613
9,520,711
9,837,913
9,913,346
10,098,202
10,103,538
D10CC150HV10FL
9,401,237
D10CC150HVT-F
9,237,613
9,520,711
9,837,913
9,913,346
10,098,202
10,103,538
D10CC150HVx-F
8,680,776
8,716,937
8,928,236
8,928,250
D10CC150UV10F
8,212,643
9,237,613
9,520,711
9,837,913
9,913,346
10,098,202
10,103,538
D10CC150UV-F
8,212,643
D10CC150UVT-F
8,212,643
9,237,613
9,401,237
9,520,711

9,837,913
9,913,346
10,098,202
10,103,538
D10CC150UVT-FJ
8,212,643
D10CC150UVx-F
8,680,776
8,716,937
D10CC30347TWx-X
9,237,613
9,583,073
9,668,309
9,769,890
9,820,351
9,826,583
D10CC30UNVD-C
9,237,613
D10CC30UNVPW-C
9,894,718
10,083,790
10,098,202
D10CC30UNVPW-L
9,894,718
10,098,202
D10CC30UNVPWX12-C
10,083,790
10,098,194
10,098,202
10,178,720
D10CC30UNVPWX12-K
10,098,194
10,098,202
10,178,720
D10CC30UNVPWX24-C
10,083,790
10,098,194
10,098,202
10,178,720

D10CC30UNVPWX24-K	
10,098,194	
10,098,202	
10,178,720	
D10CC30UNVPWX-C	
9,894,718	
D10CC30UNVPWX-K	
9,894,718	
D10CC30UNVTW-C	
9,237,613	
9,583,073	
9,668,309	
9,769,890	
9,826,583	
D10CC30UNVTWL	
9,237,613	
9,583,073	
9,668,309	
9,769,890	
9,826,583	
D10CC30UNVTW-L	
9,237,613	
9,583,073	
9,668,309	
9,769,890	
9,826,583	
D10CC30UNVTZ-C	
9,237,613	
9,583,073	
9,668,309	
9,769,890	
9,826,583	
D10CC30UVPID12-C	
10,045,451	
10,098,202	
10,264,641	
D10CC30UVPID24-C	
10,045,451	
10,098,202	

10,264,641	
D10CC30UVPWA12-C	
10,264,641	
D10CC30UVPWA24-C	
10,264,641	
D10CC42UNVA-A	
9,237,613	
D10CC42UNVS-A	
7,786,391	
9,237,613	
D10CC55347TW-C	
9,237,613	
9,583,073	
9,668,309	
9,769,890	
9,820,351	
9,826,583	
D10CC55347TW-K	
9,237,613	
9,583,073	
9,668,309	
9,769,890	
9,820,351	
9,826,583	
D10CC55347TZ-C	
9,237,613	
9,583,073	
9,668,309	
9,769,890	
9,820,351	
9,826,583	
D10CC55UNVA-C	
9,237,613	
D10CC55UNV-C	
9,237,613	
D10CC55UNVD-C	
9,237,613	
D10CC55UNVT-C	
8,654,485	

9,237,613	
D10CC55UNVTW-C	
9,237,613	
9,583,073	
9,668,309	
9,769,890	
9,826,583	
D10CC55UNVTZ-C	
9,237,613	
9,583,073	
9,668,309	
9,769,890	
9,826,583	
D10CC60UNVA-V	
9,190,830	
D10CC60UNV-V	
9,363,862	
D10CC60UNVV-V	
9,190,830	
D10CCT180UVT-F	
9,125,259	
D12V60UNV-A	
7,786,391	
D14CC150HVT-F	
9,237,613	
9,520,711	
9,837,913	
9,913,346	
10,098,202	
10,103,538	
D14CC150HVx-F	
8,680,776	
8,716,937	
8,928,236	
8,928,250	
D14CC150UV10F	
8,212,643	
9,237,613	
D14CC150UVT-F	

8,212,643
9,237,613
9,401,237
9,520,711
9,837,913
9,913,346
10,098,202
10,103,538
D14CC150UVx-F
8,680,776
8,716,937
D15CC55347TW-C
9,237,613
9,583,073
9,668,309
9,769,890
9,820,351
9,826,583
D15CC55347TW-K
9,237,613
9,583,073
9,668,309
9,769,890
9,820,351
9,826,583
D15CC55347TZ-C
9,237,613
9,583,073
9,668,309
9,769,890
9,820,351
9,826,583
D15CC55UNVA-C
9,237,613
D15CC55UNVD-C
9,237,613
D15CC55UNVPA12-FS
9,913,354
10,098,202

D15CC55UNVPA24-FS
9,913,354
10,098,202
D15CC55UNVPW12-C
10,083,790
10,098,202
D15CC55UNVPW24-C
10,083,790
10,098,202
D15CC55UNVPW-C
9,894,718
10,083,790
10,098,202
D15CC55UNVPW-L
9,894,718
10,098,202
D15CC55UNVPWX12-K
10,098,194
10,098,202
10,178,720
D15CC55UNVPWX24-K
10,098,194
10,098,202
10,178,720
D15CC55UNVPWX-C
9,894,718
D15CC55UNVPWX-K
9,894,718
D15CC55UNVT-C
8,654,485
9,237,613
D15CC55UNVTW-C
9,237,613
9,583,073
9,668,309
9,769,890
9,826,583
D15CC55UNVTW-L
9,237,613

9,583,073
9,668,309
9,769,890
9,826,583
D15CC55UNVTZ-C
9,237,613
9,583,073
9,668,309
9,769,890
9,826,583
D15CC55UVPA12-FS
9,837,194
D15CC55UVPA24-FS
9,837,194
D15CC55UVPID12-C
10,045,451
10,098,202
10,264,641
D15CC55UVPID24-C
10,045,451
10,098,202
10,264,641
D15CC55UVPWA12-C
10,264,641
D15CC55UVPWA24-C
10,264,641
D21CC80347TW-D
9,237,613
9,583,073
9,668,309
9,769,890
9,820,351
9,826,583
D21CC80347TZ-D
9,237,613
9,583,073
9,668,309
9,769,890
9,820,351

9,826,583
D21CC80UNVPW-C
9,894,718
10,083,790
10,098,202
D21CC80UNVPWX12-D
10,083,790
10,098,194
10,098,202
10,178,720
D21CC80UNVPWX24-D
10,083,790
10,098,194
10,098,202
10,178,720
D21CC80UNVPWX-D
9,894,718
D21CC80UNVTW-D
9,237,613
9,583,073
9,668,309
9,769,890
9,826,583
D21CC80UNVTZ-D
9,237,613
9,583,073
9,668,309
9,769,890
9,826,583
D21CC80UVPID12-D
10,045,451
10,098,202
10,264,641
D21CC80UVPID24-D
10,045,451
10,098,202
10,264,641
D21CC80UVPWA12-D
10,264,641

D21CC80UVPWA24-D
10,264,641
D23CC90HRVT-F
9,237,613
D23CC90UNVT-F
9,203,321
9,237,613
D24V100UNV-A
7,786,391
D28CC95UVPA12-F
9,837,194
9,913,354
10,098,202
D28CC95UVPA12-FS
9,913,354
9,978,496
10,098,202
D28CC95UVPA12-VF
9,837,194
9,913,354
9,978,496
10,098,202
D28CC95UVPA12-VJ
9,913,354
9,978,496
10,098,202
D28CC95UVPA24-F
9,837,194
9,913,354
10,098,202
D28CC95UVPA24-FS
9,913,354
9,978,496
10,098,202
D28CC95UVPA24-VF
9,837,194
9,913,354
9,978,496
10,098,202

D28CC95UVPA24-VJ
9,913,354
9,978,496
10,098,202
D530C150HV10F
9,237,613
9,520,711
9,837,913
9,913,346
10,098,202
10,103,538
D530C150HV-F
9,237,613
9,520,711
9,837,913
9,913,346
10,098,202
10,103,538
D530C150HVT-F
9,237,613
9,520,711
9,837,913
9,913,346
10,098,202
10,103,538
D530C150HVx-F
8,680,776
8,716,937
8,928,236
8,928,250
D530C150UV10F
9,237,613
9,520,711
9,837,913
9,913,346
10,098,202
10,103,538
D530C150UV-F
9,520,711

9,837,913
9,913,346
10,098,202
10,103,538
D530C150UVT-F
9,237,613
9,401,237
9,520,711
9,837,913
9,913,346
10,098,202
10,103,538
D530C150UVx-F
8,680,776
8,716,937
D530CC150UV10F
8,212,643
D530CC150UVF
8,212,643
D530CC150UVT-F
8,212,643
D700C120UVT-V
9,237,613
D700C120UVx-V
9,190,830
D700C150HV10F
9,237,613
9,520,711
9,837,913
9,913,346
10,098,202
10,103,538
D700C150HV10FL
9,401,237
D700C150HVT-F
9,237,613
9,520,711
9,837,913
9,913,346

10,098,202
10,103,538
D700C150HVx-F
8,680,776
8,716,937
8,928,236
8,928,250
D700C150UV10F
8,212,643
9,237,613
9,520,711
9,837,913
9,913,346
10,098,202
10,103,538
D700C150UV-F
8,212,643
D700C150UVT-F
8,212,643
9,237,613
9,401,237
9,520,711
9,837,913
9,913,346
10,098,202
10,103,538
D700C150UVT-FJ
8,212,643
D700C150UVx-F
8,680,776
8,716,937
D700C20UNVPW-C
9,894,718
10,083,790
10,098,202
D700C20UNVPW-L
9,894,718
10,098,202
D700C20UNVPWX12-C

10,083,790
10,098,194
10,098,202
10,178,720
D700C20UNVPWX12-K
10,098,194
10,098,202
10,178,720
D700C20UNVPWX24-C
10,083,790
10,098,194
10,098,202
10,178,720
D700C20UNVPWX24-K
10,098,194
10,098,202
10,178,720
D700C20UNVPWX-C
9,894,718
D700C20UNVPWX-K
9,894,718
D700C30347TW-C
9,237,613
9,583,073
9,668,309
9,769,890
9,820,351
9,826,583
D700C30347TW-K
9,237,613
9,583,073
9,668,309
9,769,890
9,820,351
9,826,583
D700C30347TZ-C
9,237,613
9,583,073
9,668,309

9,769,890
9,820,351
9,826,583
D700C30UNVD-C
9,237,613
D700C30UNVTW-C
9,237,613
9,583,073
9,668,309
9,769,890
9,826,583
D700C30UNVTZ-C
9,237,613
9,583,073
9,668,309
9,769,890
9,826,583
D700CT160UVT-F
9,125,259
DCLBAC-LP1206
8,405,488
DCLBAC-LP1209
8,405,488
DCLBAC-LP1212
8,405,488
ESB216-12
8,212,643
ESB432-14
8,212,643
LP12DCLUNV-06
8,405,488
LP12DCLUNV-12
8,405,488
M7012-27CK-6EU-F
8,319,447
M7012-27CK-6EU-J
8,319,447
M7012-27CK-6EU-JT3
8,319,447

MC20DCLUNV
7,394,204
8,405,488
MC20DCLUNVDY
7,394,204
8,405,488
S3321600
8,212,643
SC20DCLUNV
7,394,204
8,405,488
SC20DCLUNVDY
7,394,204
8,405,488
SLI259IUNVHPA
7,786,391
W3V-DF-254ND
8,278,835
8,405,488
8,450,946
8,471,475
8,581,497
8,593,078
W3V-DL-254ND
8,278,835
W3V-DX-254ND
8,278,835
WDR-DF-232NA
8,405,488
8,450,946
8,471,475
WDR-DF-332LA
8,405,488
8,450,946
8,471,475
WDR-DF-332NA
8,405,488
8,450,946
8,471,475

WDR-DF-332NE
8,405,488
8,450,946
8,471,475
WDR-DF-432NE
8,405,488
8,450,946
8,471,475
WDR-LP12-00
8,405,488
WDR-LP12-04
8,405,488
WDR-LP12-12
8,405,488
WDY-CCM20
7,394,204
8,405,488
WDY-DF-232NA
8,405,488
8,450,946
8,471,475
8,581,497
8,593,078
WDY-DF-ACM
8,405,488
8,450,946
8,471,475
WDY-LP12BAC08
8,405,488
WDY-LP12BAC10
8,405,488
WDY-LP12BAC12
8,405,488
WDY-SC-CCM20
8,405,488
WRV-CCM20
7,394,204
8,405,488
WRV-CCMBAC

7,394,204
8,405,488
WRV-DF-232HA
8,278,835
8,405,488
8,441,203
8,450,946
8,471,475
8,581,497
8,593,078
WRV-DF-232NA
8,278,835
8,405,488
8,450,946
8,471,475
8,581,497
8,593,078
WRV-DL-254ND
8,278,835
WRV-DX-232HA
8,278,835
WRV-DX-232NA
8,278,835
WRV-LP14X2003

8,405,488
WRV-LP14X2004
8,405,488
WRV-LP14X2008
8,405,488
WRV-LP14X2009
8,405,488
WRV-LP14X2014
8,405,488
WRV-LP-232HA
7,786,391
8,278,835
8,405,488
WRV-LP-232NA
7,786,391
8,278,835
8,405,488
WRV-PS-232HA
7,786,391
8,278,835
WRV-PS-232NA
7,786,391
8,278,835
WRV-SC-CCM20

8,405,488
WRV-SC-CCMBAC
8,405,488
WTDCL21
8,405,488
WTDCL51
8,405,488
WUV-DF-254ND
8,405,488
8,450,946
8,471,475
8,581,497
8,593,078
WUV-DL-254ND
8,278,835
WUV-DX-254ND
8,278,835
8,405,488
8,450,946
8,471,475
8,581,497
8,593,078